

WETROOM WALLS



- └ *Waterproof installation*
- └ *Unique concept: floors, walls, borders and accessories available*
- └ *Hygienic and easy to maintain*

Technical data		Aquarelle Wall HFS	Aquarelle Wall/ Aquarelle Wall Borders
Classification	EN 259	Heavy duty	Heavy duty
Total thickness	EN 428	0.92 mm	0.92 mm
Wear layer thickness	EN 429	0.12 mm	0.12 mm
Total weight	EN 430	1 500 g/m ²	1 500 g/m ²
Dimensional stability	EN 434	Lengthwise: ≤ 0.60 mm Widthwise: ≤ 0.20 mm	Lengthwise: ≤ 0.60 mm Widthwise: ≤ 0.20 mm
Curl resultant to heat	EN 434	≤ 0.8 % ≤ 2 mm	≤ 2 mm
Reaction to fire	EN 13501-1	B-s2 d0 on gypsum plasterboard and on A1 or A2 substrate	C-s2 d0 on gypsum plasterboard and on A1 or A2 substrate
Seam strength (N/50 mm)	EN 684	≥ 150	
Acoustical absorption	NF EN ISO 354 α_w	0.05 (H)	0.05 (H)
Chemical resistance	EN 423	Good resistance	Good resistance
Resistance to bacteria	NF EN ISO 846	Sanitized ^(R) High fungi effect	Sanitized ^(R) High fungi effect
Colours		18 + 3 borders	27 + 20 borders
Form of delivery	EN 259	Rolls: 35 lm x 2 m Borders: 49 cm x 30-35 m	Rolls: 35 lm x 2 m Borders: 49 cm x 30-35 m

The above information is subject to modifications for the benefit of further improvement (01/2010).

For more detailed technical information, please contact Tarkett.


Aquarelle Wall HFS

- └ Waterproof installation, ideal for wet commercial applications
- └ Unique concept: walls, floors, borders and accessories available (compatible with Granit Multisafe)
- └ 3 colour atmospheres designed for well being
- └ Fire resistant: Bs2 d0
- └ Hygienic and easy to maintain





3942 035




3942 020




3942 034



3942 033



3942 032



3942 031



3942 030



3942 029



3942 028



3942 027



3942 019



3942 026



3942 025



3942 024



3942 023



3942 018



3942 022



3942 021