

TECSOM 4120 GALERIE




Cut-piled carpet tile
100% Solution Dyed PA Yarns



Tecsom 4120 galerie 127440505-XXXXX




00137



00098




00096



00084



00086



00088



00022



00024



00027




00062


TECHNICAL DATA

TECSOM 4120 GALERIE	
SPECIFICATION	N°127440505-XXXXX
Dimensions / Dimensions / Dimensiones	50x50 cm
Surface / Pile Fibre / Fibra	100% PA (Solution dyed)
Premier dossier / Primary Backing / Soporte primario	Non tissé / Non woven primary backing
Envers / Backing / Revés	Matières recyclées renforcées par un voile de verre, 100 % recycled vinyl backing reinforced with glass fiber
Jauge / Gauge / Galga	1/10 Cut pile
Densité / Tuft Density / Densidad	205 000 Stitches/m ² (50x41x100)
Epaisseur totale / Total Thickness / Espesor total	8,0 mm
Masse totale / Total Weight / Peso total	4835 g/m ²
Poids de fil / Total pile mass / Peso fibra	1200 g/m ²
Masse de velours utile / Mass of pile above the substrate / Peso útil	860 g/m ²
Densité du velours de surface / Surface pile density / Densidad del hilo	0,183 g/cm ³
Epaisseur velours utile / Thickness of pile above the substrate / Altura del hilo	4,7 mm

TECHNICAL PERFORMANCES		
Classification (EN 1307)	23/32 - Commercial General / LC4	
	N° 0679-CPD-0198 07 EN 14041: 2004 EN1307	
	Stabilité dimensionnelle / Dimensional Stab. / Estabilidad dimensional	≤ 0,10%
	Comportement au feu / Fire rating / Comportamiento al fuego	BflS1
Isol. Acoustique aux bruits de choc / Impact noise reduction / Absorción ruido impacto	ΔL (w) 28 dB	
Absorption acoustique / Sound absorption / Absorción acústica	aw = 0,20 (H)	
Résistance électrique / Electrostatic properties / Comp. Electrostático	< 2,0 kV RT ~ 10 ¹⁰ Ω	
Résistance thermique / Thermal resistance / Resistancia térmica	0,11 m ² KW	
Solidité à la lumière / Colour Fastness / Solidez de los colores	7/8	
Aptitude chaise à roulette / Castor Chair / Silla de ruedas	R ≥2,0-Class B	



00032



00035




00017




00149



00048



00047



00044



00078



00105



00103

